Elsafe Zenith Drawer Electronic Safes

Elsafe Zenith Drawer is the ideal electronic safe solution for properties who want to maximize convenience for their residents and encourage use of the in-room safe. It provides superior design flexibility, allowing for placement inside drawers, cupboards...or anywhere in the room that it is most accessible and easy to use.



FEATURES

- : Industry leading audit trail (500 events).
- : Flash memory.
- : Reprogrammable configuration.
- : ADA compliant telephone style keypad.
- : 4-digit code.
- : LED display for clear visible numbers.
- : Internal light.
- : Push button to lock door.
- : Powered with five (5) AA batteries.
- : Low battery warning.
- : Easy external battery change.
- : Accommodates up to 17" laptop in certain models.
- : Serviced by computerized service device with unique service code.
- : Anti-tamper labyrinth.
- : Internal carpet.
- : Unique triangular locking bolt reinforcement.
- : Easy maintenance.
- : 18 mm solid bolt locking mechanism.
- : Hydraulic arm ensures smooth and safe door movement (Top Open Safe)
- : Heavy duty sliders for smooth and safe drawer movement (Pull Out Safe).



Optional features

- : Anti tamper switch.
- : Wireless RF online communication upgrade (requires online network).
- : Rental mode by activation code.
- : Power outlet inside the safe.

ASSA ABLOY

The global leader in door opening solutions



SafeLink Software

SafeLink software is the ultimate tool to commission, maintain, and service Elsafe safes.

PinKey

PinKey is a compact electronic PIN code protected key to securely override and service Elsafe safes.



*Measurements		Zenith Top Open 15		
Outside H/W/D	mm	134 / 400 / 350	134/460 /350	191/460/466
Incl. keyboard	inches	5 ^{9/32} / 15 ^{3/4} / 13 ^{13/16}	5 ^{9/32} / 18 ^{1/18} / 13 ^{13/16}	7 ^{17/32} / 18 ^{1/8} / 18 ^{5/16}
Inside H/W/D	mm	62-124 397 347	62-124/ 457/347	157/410 /374
	inches	2 ^{7/16} - 4 ^{7/8} 15 ^{5/8} 13 ^{11/16}	2 ^{7/16} - 4 ^{7/8} / 18 / 13 ^{11/16}	5 ^{13/16} / 16 ^{1/8} / 14 ^{22/32}
Internal volume	liters	15	17	24
	cu ft	0,53	0,60	0,84
Weight	kg	8,27	9,4	18,5
	Ib	18,23	20,72	40,78

H/W/D: Height/Width/Depth

Outlets

Optional internal power outlet in different types (US, EU and UK).



• Steel thickness Pull Out:

	Color Option 1	Color Option 2	Color Option 3
Body color	Black Gray RAL 7021	Ivory RAL 1015	White RAL 9003
Front	Black Gray RAL 7021	Ivory RAL 1015	White RAL 9003

Front Black Gray RAL 7021 Ivory RAL 1015 White RAL 9003
Override: SafeLink Software and PinKey
Steel thickness Top Open15: Door: 2 mm / Body: 1,5 mm
Steel thickness Top Open17: Door: 2,5 mm / Body: 1,5 mm

Fastening method Top Open: Bottom: 4 holes / Security wire
Fastening method Pull Out: Bottom: 4 holes / Backwall: 3 holes

Door: 4 mm / Body: 1,5 mm